UNCLASSIFIED

AD NUMBER AD356868 LIMITATION CHANGES TO: Approved for public release; distribution is unlimited. FROM: Distribution authorized to DoD only; Administrative/Operational Use; 28 DEC 1964. Other requests shall be referred to Office of Naval Research, Arlington, VA 22203. AUTHORITY ONR ltr 23 Apr 1975

CONFIDENTIAL

CNA

OPERATIONS EVALUATION GROUP Study 684

Ballistic Dispersion of Mk 80 Series Bombs Delivered in Sticks by the A-4 Aircraft (U)

CENTER FOR NAVAL ANALYSES

THE FRANKLIN INSTITUTE

OPERATIONS EVALUATION GROUP
CONTRACT NORR 3732 (00)

CONFIDENTIAL

DOWNGRADED AT 3 YEAR INTERVALS DECLASSIFIED AFTER 12 YEARS DOD DIR 5200 10

THE OPERATIONS EVALUATION GROUP OF THE CENTER FOR NAVAL ANALYSES

The Operations Evaluation Group is charged with increasing the peace-time and wartime effectiveness of the Navy and Marine Corps through operations research. It engages in studies dealing with current and near-future problems in tactics, strategy logistics, force composition and weapons employment. OEG provides scientific analysts and field representatives to the divisions in the Office of the Chief of Naval Operations, to the Commandant, U.S. Marine Corps, and to operating commands ashore and at sea.

OEG, together with the Institute of Naval Studies and the Naval Warfare Analysis Group, comprise the operating divisions of the Center for Naval Analyses. CNA, both through its operating divisions as well as through its own program of research in basic methodology and analysis techniques, conducts operations and systems research for the Chief of Naval Operations, the Commandant of the Marine Corps, and certain fleet and force commanders. CNA provides advice on operational problems susceptible of quantitative analysis, including the evaluation of new weapons, operational techniques, tactics, formulations of new requirements, technical aspects of strategic planning, and the correlation of research and development programs with Navy and Marine Corps needs.

OEG publishes three principal types of reports of its research, in addition to many memoranda of limited distribution—

STUDIES, which are complete self-substantiating analyses providing the Navy or the Marine Corps with a quantitative basis for executive decisions or for recommendations to higher authority. Studies are endorsed by CNA or the operating division releasing the study, and represent the point of view held at the time of issue.

SUMMARY REPORTS, which are resumes of research originally published in another form. They present only results without substantiating analysis and are designed for general information.

* * *

RESEARCH CONTRIBUTIONS, which can be originated by any member of CNA, and in the opinion of the director of the issuing division is of interest to workers in the field of operations research or in the author's field. Although Research Contributions are intended primarily for internal CNA use, some of them receive limited Navy Department distribution.

DISC OVERLANDERS WITHOUT

U.S. Millitery again for may obtain copies of this report directly from CDA. Government again to shall request from the Office of the Close of New Commission. Other qualified users shall compare through their type suring government against to the Office of the Charl of News Constitute.

CONTRACT NONE STUDIOS

Bits muserual contons information affecting the nethronal delines of the Lithout States within the memoring of the Eppinings Lines, Talle 18, U.S.C. Section 793 and 794, the transmission or reveloping of which in may memore be un undefforted parameter problems by line.

DOWNGRADED APPROVED ART MURH COPETABSTAVY

OFFICE OF THE CHIEF OF NAVAL OPERATIONS WASHINGTON, D. C. 20350

IN REPLY BEFER TO Op03EG/ect Ser 08203 2 0 LLU 1964

OLA INFIALITY CONFIDENTIAL - UNCLASSIFIED WHEN ENCLOSURE REMOVED

Chief of Maval Operations

To:

Distribution List

Subj:

Operations Evaluation Group Study No. 684; forwarding of (U)

Encl: (1) OEG Study 684, Confidential, entitled "Ballistic Dispersion of EK 80 Series Bombs Delivered in Sticks by

the A-4 Aircraft (U)"

1. Enclosure (1), prepared by the Operations Evaluation Group of the Center for Naval Analyses, is provided for information and retention. The study represents the best opinion of OEG at the time of issue.

- 2. From test data, the study calculates the ballistic dispersion of low-drag bombs dropped in sticks from A-4 aircraft, so that ballistic dispersion as a function of delivery conditions can be better predicted.
- The Chief of Naval Operations approves this study for use by those responsible for planning attacks with low-drag bombs, pending replacement of the latter by SNAKEYE.
- 4. If additional copies are required, they will be provided upon request.
- When no longer required, this publication may be destroyed by burning. No report of destruction need be submitted.
- 6. This material contains information affecting the National defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C., Sections 793 and 794, the transmission or revelation of which in any manner to an unauthorized person is prohibited by law.

SHEWAS F CONNCLLY By direction

DISTRIBUTION: Attached List

CONFIDENTIAL

DISTRIBUTION LIST FOR OPNAV SER 08P03:

CECDEE DEPSECLER DUKOE Dir WSEG (2)

CIHCSIPIKE MAVABR, JSIPS

COMDI -FSC Dir, DIA COM DDC (20)

Director of Joint Staff COMDT HATLWARCOL

SETTIAVEBR WSEG

Department of Mavy Activities

SECHAV Comptroller, Mavy ASSTSECNAV R&D

Office of Program Appraisal, EXOS

CNO

Op09	Op93	0p50	ОрО7
090	34	506	07B
09B9	342	507	OTT
09D	05	52	72
90	05M	06C	722
91	05W	60	

SNDL

21 Fleet Commanders in Chief

22 Fleet Commanders

24A Naval Air Force Commands

26F Operational Test and Evaluation Force Commands, Detachments and

Divisions (COMOPTEVFOR, COMKWESTEVDET, DEPCOMOPTEVFORPAC only) 28A Carrier Divisions

42A Fleet Air Commands

42J1 Attack Carrier Air Wings and Readiness Attack Carrier Air Wings

428 Air Development Squadrons (VX-4, VX-5 only)

45V Brigades (CGFIRSTMARBRIG)

46A Marine Air Commands 46B Marine Aircraft Wings

50A Unified Commands (CINCPAC, CINCLANT only)

E4 DIR NRL

J84 SUPTNAVPGSCOL

PRESNAVWARCOL (2) J95 J111 NUWPNTRACEN

CONAVAIRDEVCEN W7E

W7P CONWL W7S COMNOTS

BUWEPS	BUSHIPS	ONR

405 A 300 В 461

CW R

R-12

R-14

R-5

RM-3

DISTRIBUTION LIST FOR OPNAY SER 08P03

MARINE CORPS ACTIVITIES

COMPTMARCORPS (Code AX)
COMPTMARCORPS COLQUANT

Dir, MCLEDC, Quantico Dir, MCEC

DEPT OF AIR FORCE ACTIVITIES

Dept of AF(8) (Attn: PDO 4008)
USAF Liaison Office, Rand Corp.
C/S, U.S. Air Force (AFX-PDB)
COMDT, Air University
Headquarters, Fifth Air Force (PF00A)
Commander Pacific Air Forces (PF00A)
Commander APGC
HO TAC (0A0)

DEPT OF ARMY ACTIVITIES

Dept of Army (C/RD) (for RAC) Dept of Army (Adj Gen) (6)

OR DENTINE

OPERATIONS EVALUATION GROUP

STUDY NO. 684

BALLISTIC DISPERSION OF MK 80 SERIES BOMBS DELIVERED IN STICKS BY THE A-4 AIRCRAFT (U)

By: S.K. Dietz. Operations Evaluation Group

Approved by:

W.G. Leight, Operations Evaluation Group

28 December 1964

This study represents the view of the Operations Evaluation Group at the time of issue. It does not necessarily reflect the official opinion of the Chief of Naval Operations except to the extent indicated in the forwarding letter. It includes information of an operational rather than a technical nature, and should be made available only to those authorized to receive such information.

Enclosure (1) to CNO ltr Ser 08P03 Dated 28 December 1964

> Prepared by the OPERATIONS EVALUATION GROUP Center for Naval Analyses

> > COURING THAT


F-10-12

AND DESCRIPTION OF THE PARTY OF

APPROVED FOR PUBLIC RELEASE

ABSTRACT

The ballistic dispersion of low drag bombs dropped in sticks from the Λ -4 aircraft is calculated from test data. The data is inadequate to permit determination of whether dispersion depends on slant range or time of fall, but an estimate can be made for delivery parameters of interest.





COMPRETED TO

I. INTRODUCTION

Kill probability in stick bombing is a function of aiming accuracy, target vulnerability, bomb reliability, the nominal distance between bombs in the stick, and the ballistic dispersion of the bombs. The kill probability resulting from a set of these variables can be determined in a number of ways; the computer program of reference (a) is an example.

The importance of ballistic dispersion is illustrated by figure 1, computed using reference (a). The aiming accuracy used in figure 1 is typical of that achieved in 20° glide attacks using contact-fuzed low drag bombs (reference (b)); the target is a revetted jet fighter with a vulnerable area of 23,600 square feet (reference (c)).

As seen in figure 1, the effectiveness of 6 Mk 81 low drag bombs varies greatly as a function of ballistic dispersion and the spacing between bombs. The kill probability for very low ballistic dispersion (5 feet in the plane normal to the bomb trajectory) can be as much as 40 percent greater than that achievable if dispersion is as great as, say, 60 feet. Moreover, for any given dispersion, the kill probability depends on the choice of bomb spacing. In the example, changing the spacing and dispersion can change kill probability by as much as a factor of three. If the ballistic dispersion is definitely known to be less than or equal to 45 feet, optimum spacing is on the order of 100 feet (variation between 80 and 120 feet will not markedly affect kill probability for the particular target/ delivery illustrated). However, for this optimum spacing kill probability is sensitive to the value of ballistic dispersion. For ballistic dispersions known to be between 45 and 90 feet, any spacing up to 120 feet yields close to optimum results. For greater ballistic dispersions, a salvo (i.e., zero spacing between bombs) produces the best results. A knowledge of bomb dispersion is therefore a prerequisite to recommending intervalometer settings to produce the desired bomb spacings and to providing inputs for estimating force requirements.

The purpose of this study is to analyze data obtained in recent A-4 bomb drops by Air Development Squadron Five to determine a relationship by which ballistic dispersion can be predicted as a function of delivery conditions. However, measuring ballistic dispersion in range requires an accurate knowledge of the nominal (dispersion-free) distance between bombs in a stick. The inadequacy of current theoretical methods for determining bomb spacing is shown in reference (d). The analysis in this study, therefore, deals primarily with ballistic dispersion in deflection.



APPROVED FOR PUBLIC RELEASE




FIG. 1: EFFECTIVENESS OF 6 MK 81 LOW DRAG BOMBS AS A FUNCTION OF BALLISTIC DISPERSION AND BOMB SPACING

DOWNGRADED APPROVED FOR PUBLIC RELEASE

CORPORTING

If it is true, as usually assumed, that ballistic dispersion is circularly distributed around the bomb trajectory, then knowledge of deflection dispersion permits prediction of dispersion in range. Reference (c) assumes that ballistic dispersion is circularly-normally distributed about the bomb trajectory and that it is a linear function of slant range, and that low drag bombs of the Mark 80 series display a dispersion of 3 mils* normal to the trajectory. Using the empirically-adjusted bomb spacing formula developed in reference (d), range ballistic dispersion is calculated by a method derived in this study, for the narrow range of delivery conditions into which over half of the data falls. This calculation confirms the assumption of equal range and deflection ballistic dispersion in the normal plane.

^{*}With a 3 mil ballistic error, standard deviation of ballistic error is 3 x 10^{-3} x slant range.

DOWNGRADED APPROVED FOR PUBLIC RELEASE

CONFIDENTIAL

II. CONCLUSIONS

- For release at slant ranges between 3100 and 3800 feet, or for a time of fall of 4 to 5 seconds, ballistic dispersion is 15 to 20 feet for Mk 81 bombs dropped from an A-4. These slant ranges and times of fall correspond to those resulting from the standard tactics used in 20° and 30° contact-fuzed, high speed glide deliveries and 45° delay-fuzed delivery.
- An effective technique is developed for calculating ballistic dispersion in range from stick bombing impact data.
- Analysis of test data confirms the customary assumption that range and deflection ballistic dispersion are equal in a plane normal to the trajectory.
- The available data is inadequate to validate the theory that ballistic dispersion is a linear function of slant range or, alternatively, that it is a function of time of fall.
- Additional data is required to formulate a theory for predicting ballistic dispersion on the basis of radically different release conditions. However, in view of the prospective replacement of low-drag bombs by Snakeye, the required large number of drops of low drag bombs does not appear warranted.

DOWNGRADED APPROVED FOR PUBLIC RELEASE

COMPRESSION OF

III. THE TEST DATA

The test data analyzed in this study was obtained from 13 sticks of bombs dropped by Air Development Squadron Five (VX-5) in 1962 and 1963 using Λ -4 aircraft equipped with the Douglas Multiple Carriage Bomb Rack (MBR). The data has been divided into 2 sources which have the following distinguishing characteristics:

Data Source 1

- Of 12 runs which were made, 4 were rejected because of inadequate camera coverage.
- Mk 86 water/sand-filled (WSF) bombs were dropped.
- · Two bombs, which were unstable due to leakage, were excluded.
- · Delivery conditions were recorded by Askania camera coverage.
- Airspeed at release varied from 300 to 400 knots.

Data Source 2

- · Five runs were made.
- Mk 81 and 82 inert (plaster-filled) bombs were dropped.
- Five bombs which oscillated persistently and appeared unstable were included.
- · Delivery conditions were recorded by radar tracking.
- · Airspeed at release was 450 knots for all drops.

The 2 sources of data have the following common characteristics:

- One stick of bombs was dropped on each run; most sticks consisted of 6 bombs.
- A constant-speed, constant-dive angle delivery was employed.
- The MBR intervalometer controlling bomb release was set at 0.06 seconds.
- All passes were made over a bull-dozed path leading to a clearly-marked range target.

The data has been reduced on an individual stick basis with standard deviation in deflection (i.e., deflection ballistic dispersion) computed for each stick, rather than for all bombs dropped. This was done for 2 reasons: first, it is essential

CONCINCIALIVI

APPROVED FOR PUBLIC RELEASE

COMPRESENTIAL

to treat separately those runs where delivery conditions differ markedly; second, not all aircraft were directly over the bull-dozed path and cross-range wind undoubtedly differed from stick to stick. This has the effect of introducing a constant offset for each stick; however, the offset differs from stick to stick. Measurement of the standard deviation of deflection ballistic dispersion for each stick is not affected by this offset, whereas the over-all standard deviation computed for all sticks combined would be influenced by the offset.

The release conditions, vacuum trajectory parameters (computed by the method of reference (e)), and standard deviation of ballistic dispersion for each stick are given in table I; the raw impact data is summarized in appendix A.

Ballistic dispersion in deflection, $S_{\mbox{\footnotesize{BD}}}$, was determined from the formula given below and illustrated in figure 2.

$$S_{BD} = \left[\frac{\sum (Z_i - \overline{Z})^2}{n-1} \right]^{1/2}$$

where Z_i = the impact distance of the i^{th} bomb measured from a reference line parallel to the flight path

 \overline{Z} = the mean distance of bomb impact from the reference line

n = the number of bombs in the stick.

Table I shows that the inclusion or exclusion of unstable bombs makes very little difference in the ballistic dispersion of the sticks of data source 2. Therefore, and because the inert bombs in this data source presumably approximate the behavior of bombs used in combat, this analysis will include the unstable bombs of data source 2. The 2 unstable bombs of data source 1 will still be excluded, however, since their behavior is attributed to water or sand leaks and thus is not typical of live bombs.




Vacuum

TABLE I DELIVERY CONDITIONS AND BALLISTIC DISPERSION

		Release Conditions		Trajectory Parameters		Deflection Ballistic Dispersion		
Data Source	Run	Dive Angle (Degrees)	Speed (Knots)	Altitude (Feet)	Time of Fall (Sec)	Slant Range (Feet)	Number	S _{Ballistic} Dispersion (Feet)
1	1	0	304	2532	12.5	6925	6	31.0
	2	24.7	318	2382	7.1	4187	4	12.7
	3	34.8	303	2483	6.3	3632	5	16.4
	4	23,1	366	2531	7.1	4759	5	50.7
	5	42.4	396	2439	4.6	3347	6	16.2
	6	26.9	337	2486	6.8	4246	6	24.6
	7	21.8	409	2356	6.5	4795	6	29.6
	8	42.7	400	2241	4.3	3080	6	17.6
2	1	32.5	450	2200	4.6	3661	4 (6)*	9.1 (7.9)*
	2	27.5	450	1830	4.3	3455	5 (6)	20.5 (20.6)
	3	41.9	450	2720	4.7	3794	5 (6)	12.0 (21.7)
	4	44.5	450	2620	4.3	3526	4 (6)	11.9 (23.4)
	5	44.5	450	2850	4.7	3818	5 (6)	17.8 (16.4)

^{*}Figure in parentheses include additional data from unstable bombs.



where: n = number of bombs in stick

 $\mathbf{Z_i}$ = deflection coordinate of $\mathbf{i^{th}}$ impact point

K = a constant separating the x axis and the flight path vector

FIGURE 2

IV. ANALYSIS

Alternatively, ballistic dispersion is sometimes assumed to be proportional to time of fall, rather than slant range. Figure 4 shows sample ballistic dispersion against time of fall. As with slant range, there is substantial scatter and no clearout correlation, which can also be attributed to the small sample size (as shown by the 90 percent confidence intervals).

The problem of small samples can to some extent be overcome by pooling the data from those sticks released under similar conditions. Table II summarizes groups of similar slant ranges; similarly, runs are grouped by time of fall in table III.

In table IV, the average ballistic dispersion is given for each slant range group separated by data source and with the 2 sources combined. This table shows that the deflection ballistic dispersions of the 2 data sources are comparable for the 2 common slant range groups. However, an over-all difference between the 2 data sources stems from the erratically varying dispersion at range groups for data source 1 not covered in data source 2. Similarly, it can be seen that the time of fall groupings give comparable results for the 2 data sources in the small zone of overlap; however, wide variation in dispersion is evident for the longer times of fall represented only in data source 1.

Despite the fact that the data does not provide a method of predicting ballistic dispersion, the common slant range groups shown in table IV are representative of a number of widely used delivery tactics, as shown by table V. The analysis suggests that deflection ballistic dispersion lies between 15 and 20 feet for these tactics and slant ranges. Additional data might permit the development of a definitive method of predicting low-drag bomb dispersion for other delivery conditions, but preliminary calculations indicate that many runs would be required. In view of the imminent introduction of Snakeye, an extensive effort does not appear to be warranted.




FIG. 3: BALLISTIC DISPERSION AS A FUNCTION OF SLANT RANGE




FIG. 4: BALLISTIC DISPERSION AS A FUNCTION OF TIME OF FALL

TABLE II
SLANT RANGE GROUPINGS

Group	Runs	Slant Range	Airspeed	Release Dive Angle	Altitude
S - I	1 - 8	3080	400	42.7	2241
S - II	1 - 5	3347	396	42.4	2439
2	2 - 2	3455	450	27.5	1830
	2 - 4	3526	450	44.5	2620
S - III	1 - 3	3632	303	34.8	2483
	2 - 1	3661	450	32.5	2200
	2 - 3	3794	450	41.9	2720
	2 - 5	3818	450	44.5	2850
S - IV	1 - 2	4187	318	24.7	2382
	1 - 6	4246	337	26.9	2486
S - V	1 - 4	4759	366	23.11	2531
	1 - 7	4795	409	21.8	2356
S - VI	1 - 1	6925	304	0	2532

TABLE III
TIME OF FALL GROUPING

Group	Runs	Time of Fall	Airspeed	Release Dive Angle	Altitude
T - I	2 - 4	4.3	450	44.5	2620
	2 - 2	4.3	450	27.5	1830
	1 - 8	4.3	400	42.7	2241
T - II	2 - 1	4.6	450	32.5	2200
	1 - 5	4.6	396	42.4	2439
	2 - 3	4.7	450	41.9	2720
	2 - 5	4.7	450	44.5	2850
T - III	1 - 3	6.3	303	34.8	2483
	1 - 7	6.5	409	21.8	2356
	1 - 6	6.8	337	26.9	2486
T - IV	1 - 2	7.1	318	24.7	2382
	1 - 4	7.1	366	23.1	2531
T - V	1 - 1	12.5	304	0	2532

TABLE IV

DEFLECTION BALLISTIC DISPERSION (FEET) (GROUPED DATA)

	Slant Range*	S _{BD} (ft)/Number of Impacts					
Group	or Time of Fall#	Source 1	Source 2	Combined			
S - I	3090	17.6/6		17.6/6			
S - II	3300 - 3500	16.2/6	22.0/12	20.3/18			
S - III	3600 - 3800	16.4/5	16.2/18	16.3/23			
S - IV	4100 - 4300	20.9/10		20.9/10			
S - V	4700 - 4800	40.4/11		40.4/11			
S - VI	6921	31.0/6		31.0/6			
T - I	4.3	17.6/6	21.8/12	20.2/18			
T - II	4.6 - 4.7	16.2/6	16.3/18	16.3/24			
T - III	6.4 - 6.8	24.6/17		24.6/17			
T - IV	7.1	40.6/9		40.6/9			
T - V	12.6	31.0/6		31.0/6			
	Combined	29 /44	19 /30				

^{*}Slant range, in feet, for groups labelled "S" from table II.

[#]Time of fall, in seconds, for "T" groups listed in table III.

TABLE V
SLANT RANGES FOR COMMON A-4 DELIVERY TACTICS

Dive Angle	Tactic Airspeed	Release Altitude	Slant Range
20°	450	1800	4100
30°	450	2500	4300
45°	450	3000*	3980
20°	325	1500	3190

^{*}Delay-fuzed

Ballistic dispersion is generally assumed to be circularly-distributed around the bomb trajectory, so that range ballistic dispersion, measured normal to the trajectory should equal deflection dispersion. For stick bombing, however, the nominal (dispersion-free) spacing between bombs must be determined as a prerequisite to measuring ballistic dispersion. Reference (d) discloses problems in this area, but provides an empirically-adjusted formula for estimating nominal bomb spacing. Using this formula, as explained in appendix B, produces the results of table VI. The normalized range dispersion agrees closely with the deflection dispersion of table IV.

TABLE VI
RANGE BALLISTIC DISPERSION (NORMAL PLANE)


Group	Slant Range	S _{Ballistic} Dispersion, Range(N)	(Number of Impacts)
II	3300 - 3500	16.4 (16)	
III	3600 - 3800	15.2 (23)	
I & II Pooled		15.7 (39)*	

^{*}Two bombs included in table IV are excluded here because lack of camera coverage precluded distinguishing between bombs. This ambiguity affects the calculation of $S_{\mbox{\footnotesize{Ballistic}}}$ Dispersion, Range, but not that of

S_{Ballistic} Dispersion Deflection

- References: (a) Naval Warfare Analysis Group Interim Research Memorandum,
 NIRM 12, Usage Manual for a Computer Program to Compute
 the Effectiveness of Groups of Weapons Against Rectangular
 and Line Targets Unclassified 21 Aug 1962
 - (b) Operations Evaluation Group Study No. 659, Predicted Combat Accuracy of Conventional Air-to-Surface Weapons (U) Secret 7 Nov 1963
 - (c) NWIP 20-1 Naval Weapons Selection Aircraft (U) Appendix F, A-4 Interim Weapons Selection Data (U) Confidential
 - (d) Operations Evaluation Group Study No. 673, Bomb Spacing in A-4B/C Stick Bombing with Low Drag Bombs (U) Confidential
 - (e) OEG Research Contribution No. 51, Computer Program for Calculation of Vacuum Trajectory Parameter Unclassified 18 Feb 1964

APPENDIX A



APPENDIX A

IMPACT DATA

Tables A-I and A-II list the impact data for the 2 sources described in the text. The entries in the body of each table are the range and deflection coordinates (χ_{ij} , Z_{ij}) for the jth bomb of the ith run. Four runs of data source 1 have been rejected due primarily to inadequate camera coverage.

TABLE A-I

RANGE AND DEFLECTION COORDINATES (χ_{ij} , z_{ij}) FOR THE IMPACT POINT OF THE i^{th} BOMB OF THE i^{th} RUN

(DATA SOURCE 1)

Flt-Pass	Bom b _j	1	2	3	4	5	6
2 - 1	1	82,74	123, 67	172, 19	270, 34	312, 70	307, 106
2 - 2	2	-61, 797	18, 819	3,827	NR	92, 812	NR
2 - 3	3	-585, -33*	-412, -28	-365, 2	-392, -19	-324, 0	-307, 12
4 - 2	4	-278, 1005	-244, 928	-165, 864	-197,912	-58, 928	-220, 909*
4 - 3	5	-27, 60	44, 37	38, 14	29,33	130, 37	43, 19
1 - 2	6	375, 713	443, 692	427,712	488, 695	503, 728	513, 759
3 - 2	7	-233, 673	-196, 685	-56, 706	-148,663	-45, 672	-115, 617
3 - 3	8	-13, -118	-2, -137	-18, -145	35, -118	82, -97	62, -110

^{*}Unstable bombs NR = No Release


TABLE A-II

RANGE AND DEFLECTION COORDINATES (\varkappa_{ij} , z_{ij}) FOR THE IMPACT POINT OF THE i^{th} BOMB OF THE i^{th} RUN


(DATA SOURCE 2)

Run	Run _i Bomb	1	2	3	4	5	6
Α	1	-222, 122°	-194, 109	-141, 111*	-134, 111	-117, 129	-103, 114
В	2	-182, 9	-146, 25	-148, 5*	-128, 8	-114, 45	-123, 53
C	3	-258, 21	-225, 22	-275, -23*	-254, 6	-190,28	-176, 39
D	4	NC -180, -45*	- 60,0	NC -104, -2*	-33.5, -3	- 25, 18	- 22, 20
E	5	13, 15*	47,26	70, -9	81, 37	71,23	88,30

^{*}Unstable Bombs NC = No Camera Coverage



APPENDIX B



APPENDIX B

A METHOD FOR DETERMINING BOMB DISPERSION IN RANGE

In stick bombing, impacts are assumed to be normally distributed about idealized (dispersion-free) Mean Points of Impact (MPI), and such MPI's are assumed to be separated from an arbitrary orgin in accordance with specifiable inter-bomb spacings, given the distance from the origin to the MPI of the first bomb. The expression for specifying inter-bomb spacings is given in reference (d) as a function of delivery conditions.

The range coordinate for the jth bomb of a stick may therefore be partitioned into three components:

$$\chi_{ij} = R_{il} + C_{ij} + \epsilon_{ij}$$
,

where the subscript i indicates the run;

R_{il} is the range coordinate of the nominal point of impact of the first bomb of the ith run,

 C_{ij} is the separation between MPI's for bomb 1 and j , and

 ε_{ij} is an independent, normally distributed random variable with standard deviation equal to bomb dispersion in range, $\sigma_{\!RR}$.

A new set of variables, w_{ij} , can be constructed from the χ_{ij} such that each w_{ij} has the form $w_{ij} = \mu_i + \varepsilon_{ij}$, where μ_i is the population mean distance from arbitrary orgin to the expected center of the stick. The set of w's, whose variance is an unbiased estimate of range ballistic variance, can be constructed as follows:

$$w_{ij} = x_{ij} + K_{ij}$$

where Kij is given by the following table:

TABLE B-I

j	K
1	$+3S_{L/2} + S_S + 22.0/\sin \varphi_i$
2	+ $S_{L/2} + S_S + 5.5/\sin \varphi_i$
3	+ $S_{L/2}$ + 1.8/sin φ_i
4	- $S_{L/2} + 6.2/\sin \phi_i$
5	- $(S_{L/2} + S_S)$ -17.1/sin ϕ_i
6	- (3 $S_{L/2}$ + S_S) - 6.5/sin ϕ_i

The spacings, $\mathbf{S}_{\mathbf{L}}$ and $\mathbf{S}_{\mathbf{S}}$, are generated by the theoretical expression derived in reference (d) and depend on delivery conditions for a given pass. The remainder of K_{ij} represents a correction factor computed in reference (d) to adjust for discrepancies between theoretical and observed spacings. Figure B-1 illustrates the relationships among these parameters and correction factors.

The sample variance of the
$$w_{ij}$$
 for a fixed run can be expressed as:
$$S_i^2 = \sum_{j=1}^n \frac{\left(w_{ij} - \mu_i\right)^2}{n_i} \quad \text{where } n_i \text{ is the number of bombs in } i^{th} \text{ stick.}$$

Although μ_i is unknown, it can be estimated by \overline{w}_{ij} with the loss of only one degree of freedom in the calculation as follows:

$$\overline{S}_{i}^{2} = \sum_{j=1}^{n} \frac{(w_{ij} - \overline{w}_{ij})^{2}}{n_{i} - 1}$$
.

The sample bomb dispersion in range, $\overline{S}_i = S_{BR}$, computed for the i^{th} run, is measured in the ground plane. The normal plane range dispersion, SBR(N), can be calculated as $S_{BR(N)} = S_{BR} \sin \phi$, where ϕ is the impact angle (measured from the horizontal) of the bomb's velocity vector. Each sample variance is an estimate of the range ballistic variance, σ_{BR}^{2} . If these variances come from the same population, they can be pooled as follows:




FIG. B-1: SCHEMATIC ILLUSTRATION OF RANGE COORDINATES (χ_{ij}) OF ACTUAL IMPACTS OF A TYPICAL STICK, NOMINAL (DISPERSION FREE) IMPACTS(O'S) AND POPULATION MEAN AT THE EXPECTED CENTER OF THE STICK, ALL MEASURED FROM AN ARBITRARY ORIGIN

$$S_{\text{pooled}}^{2} = \frac{\sum_{i=1}^{\overline{\Sigma}} (n_i - 1) \overline{S}_i^{2}}{\sum_{i=1}^{\overline{\Sigma}} (n_i - 1)}$$

This is an estimate of σ_{BR}^{-2} with degrees of freedom equal to the total number of bombs dropped minus the number of passes. The assumption that the variances can be pooled is valid only if the variation in delivery conditions from run to run does not significantly change the corresponding population variance for bomb distributions. This requirement is met when the same delivery tactic is used for every run. (It could also be true when the delivery conditions vary from run to run if bomb dispersion is independent of delivery conditions.)

The pooled value for normal plane bomb dispersion in range can be calculated by the above method using $S_{BR(N)}$ instead of S_{BR} for $\overline{S_i}$. This procedure is valid even for different delivery conditions which produce different σ_{BR} , as long as slant range is nearly equal for all runs so that $\sigma_{BR(N)}$ remains constant.

